

C/87

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION
Drawer DD
Artesia NM 88210

5. LEASE
LC-028784-c

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Keely Fed C

9. WELL NO.
47

10. FIELD OR WILDCAT NAME
Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 13, T-17-S, R-29-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3643.5'KB 3634'GL

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 5-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR PHILLIPS OIL COMPANY
Successor to General American Oil co. of TX

3. ADDRESS OF OPERATOR
4001 Penbrook St., Odessa, Texas 79762

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980'FNL & 1980'FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input checked="" type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Perforate the Grayburg from $\pm 2300'$ - $2500'$.
2. Fracture treat the Grayburg w/refined oil.
3. Return well to production.

Subsurface Safety Valve: Manu. and Type N/A Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE March 30, 1984

(This space for Federal or State office use)
APPROVED BY P. R. [Signature] TITLE P.E. DATE 6/6/84
CONDITIONS OF APPROVAL, IF ANY: