

NOV 17 1995

OIL CONSERVATION DIV
S. 1st ST.
ARTESIA, NM 88210-2834

CLSF

Form 3160-5
(November 1989)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

5. Lease Designation and Serial No.
LC 028784-B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

NM NM 88525 X

8. Well Name and No.

Burch Keely Unit #7

9. API Well No.

30-015-20562

10. Field and Pool, or Exploratory Area

Brbg Jackson SR Q Grbg S

11. County or Parish, State

Eddy, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

MARBOB ENERGY CORPORATION

3. Address and Telephone No.

P. O. Artesia, NM 88210 (505) 748-3303

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 1893' FWL Sec. 18 T-17-S R-30-E UNIT C.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) 4 1/2 CIBP set @ 2468' cap with 35' cement
- 2) Load hole with mud
- 3) Perforate 4 1/2 casing @ base of salt 987' squeeze with 50 sacks cement W.O.C.
Tag cement top @ 881'
- 4) Perforate 4 1/2 casing @ top of salt 555' squeeze with 50 sacks cement W.O.C.
Tag cement top @ 432'
- 5) Perforate 4 1/2 casing @ 60' circulate cement to surface between 4 1/2 & 8-5/8
& open hole
- 6) Job completed 11-01-95

RECEIVED

JAN 18 1996

OIL CON. DIV.
DIST. 2

Post ID-2
12-29-95
YKA

14. I hereby certify that the foregoing is true and correct

Signed Elvira Kleck

Title District Secretary

Date 11-13-95

(This space for Federal or State office use)

Approved by Chris Signed by Adam Salameh
Conditions of approval, if any:

Title Petroleum Engineer

Date 11/17/96