

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPL. E*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

1C-028793-a

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Burch "A"

9. WELL NO.

28

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

10 - 17S - 30E

12. COUNTY OR
PARISH

Eddy

13. STATE

New Mexico

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW
WELL ☒WORK
OVER ☐DEEP-
EN ☐PLUG
BACK ☐DIFF.
RESVR. ☐Other ☐

RECEIVED

2. NAME OF OPERATOR

General American Oil Company of Texas ✓

3. ADDRESS OF OPERATOR

P. O. Box 416 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface

990' FSL and 330' FWL

Sec. 18, T17S, R30E

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

3-28-73

16. DATE T.D. REACHED

4-3-73

17. DATE COMPL. (Ready to prod.)

4-17-73

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3632' GL

19. ELEV. CASINGHEAD

3631

20. TOTAL DEPTH, MD & TVD

3300'

21. PLUG, BACK T.D., MD & TVD

3294'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0 - 3300'

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

2443' - 3078' Grayburg & San Andres

25. WAS DIRECTIONAL
SURVEY MADE

NO

26. TYPE ELECTRIC AND OTHER LOGS RUN

SWN, Gr & Caliper

27. WAS WELL CORED

NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	20	460' KB	12 1/4"	100 sacks	NONE
4 1/2"	9.5	3300' KB	7 7/8"	320 sacks	NONE

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8" OD	EUE 3244'	

31. PERFORATION RECORD (Interval, size and number)

2443'-2451'; 2509'-2512'; 2552'-2557';
2625'-2630'; 2780'-2788'; 2986'-2988';
2998'-3000'; 3022'-3024'; 3070'-3078'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
See Reverse Side	

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
April 17, 1973		Pumping				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
4-19-73	24		→	80	96	75 L. W.	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL—API (CORR.)	
		→	80	96	75 L. W.		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold to Phillips

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

Logs & Deviation Survey

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

J. E. Hallett

TITLE

District Superintendent

DATE

April 25, 1973

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Frased from	3070'	3078'	With 30,000# sand and 30,000 gallons water.	Queen	1962	+1680
Acidized from	2986'	3024'	With 3,000 gallons.			
Frased from	2780'	2788'	With 30,000# sand and 30,000 gallons water.			
Acidized from	2625'	2630'	With 2,000 gallons.			
Frased from	2509'	2557'	With 30,000# sand and 30,000 gallons water.			
Frased from	2443'	2451'	With 20,000# sand and 20,000 gallons water.			
Loco Hills	2435'	2455'	Sand.	San Andres	2672	+ 970
Metax	2508'	2598'	Sand Stringers.	Lovington	2775	+ 867
Braybury Dolo.	2624'	2631'	Dolomitic sands			
Lovington	2775'	2788'	Sand			
San Andres	2930'	3080'	Dolomitic - zones of porosity.			

BURCH A 28

Deviation Survey

<u>DEPTH</u>	<u>DEGREES</u>
1410'	1 1/2°
1647'	1 1/2°
2145'	1°
2617'	1 1/4°
3300'	1 1/4°

This is a true and correct report to the best of my knowledge.

W. E. Hutter

Signed before me this 25 day of April, 1973.

Frank P. Quinn

Notary Public

My Comm. Expires 12/31/74

