

Copy 257

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLA FE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
LEASE DESIGNATION AND SERIAL NO.

NM 7747

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME Square Lake 12 Unit
2. NAME OF OPERATOR Kewanee Oil Company		8. FARM OR LEASE NAME Tract 6B
3. ADDRESS OF OPERATOR P. O. Box 3786, Odessa, Texas 79760		9. WELL NO. 6
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit C 990' FNL & 1980' FWL, Section 12- T-17-S, R-29E, Eddy County, New Mexico		10. FIELD AND POOL, OR WILDCAT Square Lake G-SA
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3652' G.R.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 17 17
		12. COUNTY OR PARISH Eddy
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to T.D. 2601' G.L. Cemented 5-1/2, 14#, J-55, API csg. @ 2596.65' G.L. with 425 sx. Class C with 6% gel, 100 sx Class H with 3/4% CRF-2, 5# salt per sack, 10# sand per sack and 1/4# Flo-Seal per sack. Plug did not bump. Temperature survey found plug @ 1600' G.L., no cement behind pipe. Drilled plug and cement to PBTD 2573' G.L. Ran cement bond log and Gamma Ray-Neutron log. Good cement bond 2488' to 2573' G.L. Set retainer @ 1550'. Cemented with 70 sacks 50% Cal-Seal & 50% Class H & 150 sacks Class H with 5% CFR-2, 10# sand per sack. Waited on cement 36 hours. Drilled retainer and cement to 1656'. Pipe did not test. Set retainer @ 1547'. Cemented with 150 sacks Class C with 4% CaCl. Cleared tool and waited on cement 18 hours. Cemented with 150 sacks Class C with 3# sand per sack and 150 sacks Class C neat @ max. pressure 1800 psi. Waited on cement 48 hours. Drilled retainer and cement to 1630'. Tested 5-1/2" casing @ 1000 psi for 30 minutes. No loss in pressure. Work performed 6-10-73 to 6-18-73. Verbal approval by Mr. Knauf prior to work.

RECEIVED
JUN 20 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED E. F. Stinson

TITLE District Manager

DATE 6-19-73

(This space for Federal or State office use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE JUN 20 1973

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963 O-685229

847-485