

three minutes of test.

NO VISIBLE LEAK. PRESSURE LEVELING OUT TOWARDS APPROXIMATELY 4900#.

---

RETEST: Chokeline-Manifold same as before but with inside valve closed next to stack on chokeline and all valves closed off choke-manifold cross - pressure applied as before.

Test #4 Pressured to 5000# with same leak to flange at guage connection. Tightened.

Test #5 Repeated test. Pressured to 5000# with loss of approximately 50# during first ten minutes then leveling out for remaining two minutes of test.

NO VISIBLE LEAK. PRESSURE STEADY AT APPROXIMATELY 5000#.

---

TESTING: Blind Rams with outside valve closed off stack on kill line and all valves closed off choke-manifold cross - pressure applied as before.

Test #6 Pressured to 5000# with leak to flange between stack and inside valve next to stack on kill line and leak to "O" ring of operating arm shaft of blind rams bop (pit side). Tightened.

Test #7 Repeated test. Pressured to 5000# with same leak to "O" ring of operating arm shaft of blind rams bop (pit side). Replaced "O" ring.

Test #8 Repeated test. Pressured to 5000# with same leak. Repacked.

Test #9 Repeated test. Pressured to 5000# with loss of approximately 50# during first eight minutes then leveling out for remaining five minutes of test.

NO VISIBLE LEAK. PRESSURE STEADY AT APPROXIMATELY 5000#.

Released pressure to 4600# and opened outside valve off stack