

COPIES RECEIVED	3
DISTRIBUTION	
TA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

OCT 15 1974

O. C. C.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	NM-2747	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator WINDFOHR OIL COMPANY ✓	8. Farm or Lease Name Jackson "B"
3. Address of Operator 1202 First National Bank Bldg, Fort Worth, Texas 76102	9. Well No. 29
4. Location of Well UNIT LETTER <b>K</b> , <b>1980</b> FEET FROM THE <b>south</b> LINE AND <b>1830</b> FEET FROM THE <b>West</b> LINE, SECTION <b>1</b> TOWNSHIP <b>17S</b> RANGE <b>30E</b> NMPM.	10. Field and Pool, or Wildcat Square Lake
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Bddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <u>Side track junk</u> <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

While coring at a depth of 3007', core barrel twisted off and we are unable to recover the stuck barrel. It is proposed to place a cement plug from top of fish at 2975' back to 2775'. Cement will be Class "C" with 2% CaCl + 10% sand. Hole will then be side-tracked in order to drill around core barrel.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Raymond L. Gray TITLE Consulting Engineer DATE Oct. 10, 1974  
 APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE OCT 16 1974  
 CONDITIONS OF APPROVAL, IF ANY: