

8. ANCILLARY FACILITIES:

A. None anticipated.

9. WELLSITE LAYOUT:

A. The wellsite was originally staked 1980' from the north line of the section but was moved 140' north because the Amoco pipeline crossed the well pad. See Exhibit "D".

B. The wellsite has been surveyed, staked and flagged.

C. The dimensions and relative location of the drill pad, mud pit, and trash pit with respect to the well bore are shown on Exhibit "D".

D. The ground surface slopes to the northeast. There will be approximately a 3' cut at the SW corner, approximately a 1' cut at the NW corner, approximately a 2' fill at the NE corner, and approximately a 1' cut at SE corner.

E. The well pad will be surfaced with caliche.

10. PLANS FOR RESTORATION OF THE SURFACE:

A. After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed. Pits will be filled and the location cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing condition as possible.

B. Any unguarded pits containing fluids will be fenced until they are filled.

C. After abandonment, all equipment, trash and junk will be removed and the location cleaned. Any special rehabilitation and/or special revegetation requirements of the surface management agency will be complied with and accomplished as expeditiously as possible.

11. OTHER INFORMATION:

A. Topography: The terrain at the drillsite slopes to the northeast. Bear Grass Draw is 1½ miles to the east. See Exhibit "B".

B. Soil: Sandy clay loam.