

Liquid - 3880
 Prop. - 15797
 Per. - 28509

adg

IT IS THEREFORE ORDERED THAT: ADMINISTRATIVE ORDER NO. WFX-604

February 13, 1991

The applicant, Burnett Oil Company, Inc., be and the same is hereby authorized to inject water into the Seven Rivers-Queen-Grayburg-San Andres formation at approximately 2786 feet to approximately 3513 feet through 2 3/8-inch plastic lined tubing set in a packer located approximately 100 feet above the uppermost injection perforation in the wells shown on Exhibit "A" attached hereto for purposes of secondary recovery.

EXHIBIT "A"
 BURNETT OIL COMPANY, INC.
 GISSLER B-11 WATERFLOOD PROJECT
 INJECTION WELLS
 ADMINISTRATIVE ORDER WFX-604

Well Number	Location	Unit	S-T-R	Injection Perforations	Packer Depth	Tubing Size	Injection Pressure
Gissler "B" No. 16	1980' FSL & 660' FWL	L	11-17S-30E	2863' - 3122'	2813'	2-3/8	573 PSIG
Gissler "B" No. 18	1980' FSL & 1980' FEL	J	11-17S-30E	2982' - 3468'	2932'	2-3/8	596 PSIG
Gissler "B" No. 21	1980' FNL - 1980' FWL	F	12-17S-30E	2896' - 3463'	2846'	2-3/8	579 PSIG
Gissler "B" No. 22	660' FSL - 1880' FWL	N	11-17S-30E	2903' - 3513'	2853'	2-3/8	581 PSIG
Gissler "B" No. 23	660' FNL - 660' FWL	D	14-17S-30E	2827' - 3430'	2777'	2-3/8	565 PSIG
Gissler "B" No. 26	1980' FNL - 1980' FWL	F	14-17S-30E	2786' - 2891'	2736'	2-3/8	557 PSIG
Gissler "B" No. 27	1980' FSL - 685' FWL	L	12-17S-30E	2981' - 3031'	2931'	2-3/8	596 PSIG

10-13-87
 QN - Cased Hole
 16.0 - 3524.0
 CEMENT BOND LOG - VDL
 1100.0 - 3514.0
 CEMENT EVALUATION
 1136.0 - 3517.0