

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI-DATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

215F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

OCT 03 '88

O C D

STEEL OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

LC-029435-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. L. Keel "B"

9. WELL NO.

42

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6-T17S-R31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3757' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9/7-8/88 Spudded @ 11:00 a.m. 9/7/88. Drilled 12 1/4" hole to 463'. Ran 11 jts. 8 5/8" 24# J-55 8rd casing and set @ 463'. Cemented w/300 sx. Class "C" w/2% CC. Circulated to within 10' of surface. Cement dropped to 75' from surface. Ran 1" and pumped 65 sx. Class "C" w/2% CC. Circulated to surface, then level dropped. Pumped 30 sx. Class "C" w/2% CC. Circulated 10 sx. to pit. WOC 14 1/4 hrs. Tested BOP and shoe to 500 psi for 30 min. - held okay. Drilled out with 7 7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Superintendent

DATE 9/19/88

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS