Form 3160-5 (June 1990)

any matter within its jurisdiction.

UN ED STATES DEPARTMENT OF THE INTERIOR

AON.	-KÝ
MENDED TO SHOW SPUD DATE	(4)
COPY EDDM APPROVED	

BUREAU OF LAN	D MANAGEMENI	CONS Expires March 31, 1993	
SUNDRY NOTICES AND Do not use this form for proposals to drill or to Use "APPLICATION FOR PE	D REPORTS ON WELLS deepen or reentry to a different reservor?	Expires March 31, 1993 States Designation and Serial No. LC 029426-B	
Use "APPLICATION FOR PE	ERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name	
SUBMIT IN T	RIPLICATE	NA	
		7. If Unit or CA, Agreement Designation	
Type of Well ☑ Oil ☐ Gas ☐ Other Well ☐ Well		NA	
2. Name of Operator		8. Well Name and No.	
DEVON ENERGY CORPORATION (NEVADA) 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		WEST "B" #59 9. API Well No. 30-015-27318	
		2625' FSL & 2625' FWL, Sec 10-T17S-R31E	
2025' FSL & 2025' FWL, Sec 10-1175-RS1E		11. County or Parish, State	
		Eddy Co., NM	
CHECK APPROPRIATE BOX(s) TO	INDICATE NATURE OF NOTICE RE	PORT OR OTHER DATA	
TYPE OF SUBMISSION) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION		
Notice of Intent	Abandonment	Change of Plans	
	Recompletion	New Construction	
Subsequent Report	Plugging Back	Non-Routine Fracturing	
Trad Abandan and Marin	Casing Repair	Water Shut-Off	
Final Abandonment Notice	☐ Altering Casing ☐ Other Spud & set surface csh	Conversion to Injection Dispose Water	
	NA COM Space of the State of th	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
Spud well at 4:45 p.m. on 10-10-94. Ran 8-5/8" surface csg as follows: 5 1/2 float shoe @ 608.63'	-		
2 jts 8 5/8", 24 ppf, J-55, STC csg Float collar @ 522.58'	8		
13 jts 8 5/8", 24 ppf, J-55, STC o	esg and the same of the same o		
Cmtd csg as follows:	Reflect to	1	
165 sx 35/65 (Lite POZ; Class "C") + 6%	D20 + 2% CaCl + 1/4 lb/sk D29		
(Slurry weight = 12.7 ppg	Slurry yield = 1.93 cft/sx)	€ 0	
200 sx Class "C" + 2% CaCl			
Slurry weight = 14.8 ppg	Slurry yield = 1.32 cft/sx		
Circulated 52 sx to pit			
4. I hereby certify that the foregoing is true and correct	KAREN ROSA		
Signed Karen Roso	Title ENGINEERING TECHNICIAN	Date 11/21/94	
This space for Federal or State office use)		ACCEPTED FOR RECORD	
Approved by	Title	Date / CONTROL ONLY	
Conditions of approval, if any:		J. Jara	
		9EC 5 1994	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, actitious or fraudulent statements or representations as to any matter within its jurisdiction.