

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Charles J. Kleiner Et Al Box 230, Cisco, Texas
 Company or Operator Address
 Watson & Smith Well No. 1 in E 1/2 SW of Sec. 4, T. 18
 Lease
 R. 29, N. M. P. M., Loco Hills Field, Eddy County.
 Well is 330 feet south of the North line and 330 feet east west of the East line of Section 4
 If State land the oil and gas lease is No. Assignment No.
 If patented land the owner is H.G. Watson & O.H. Smith Address Artesia, New Mexico
 If Government land the permittee is Address
 The Lessee is Charles J. Kleiner et al Address Box 230, Cisco, Texas
 Drilling commenced August 17 19 39 Drilling was completed September 30 19 39
 Name of drilling contractor Charles J. Kleiner Address Box 230, Cisco, Texas
 Elevation above sea level at top of casing 3546 feet.
 The information given is to be kept confidential-until 19

OIL SANDS OR ZONES

No. 1, from 2450 to 2455 No. 4, from 2562 to 2635
 No. 2, from 2520 to 2525 No. 5, from 2635 to 2638 TD
 No. 3, from 2555 to 2562 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 195 to 205 feet.
 No. 2, from to feet.
 No. 3, from to feet.
 No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 1/2"	28#	8		399' 1"	Reg.				
6 5/8"	20#	8	Nat'l	2388' 11"	Reg.				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2"	390	40	Halliburton		
8 1/2"	6 5/8"	2388	100	Halliburton		3 tons

PLUGS AND ADAPTERS

Heaving plug—Material Wooden Length Depth Set 2355
 Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
7"	154	Nitro-glycerin	1080 qt.	9-24-39	2484	2638

Results of shooting or chemical treatment Result of shooting--Good

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
 Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing September 25 19 39
 The production of the first 24 hours was 180 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be approximately 37
 If gas well, cu. ft. per 24 hours approx 100M Gallons gasoline per 1,000 cu. ft. of gas
 Rock pressure, lbs. per sq. in.

EMPLOYEES

W. F. Brazelton Driller Cooper Blount Driller
 T. W. Brazelton Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 18 Cisco, Texas October 1, 1939
 day of October 19 39 Name D. G. Streater

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30		Red sandy
30	50		Red shale
50	80		Lime shells
80	85		Anhy
85	185		Chalk lime, anhy
185	195		Red bed and shells
195	205		Sand
205	250		Red bed
250	300		Lime
300	350		Red bed
350	360		Lime
360	375		Red bed
375	795		Salt
795	810		Lime
810	840		Anhy
840	860		Shells and red
860	885		Anhy
885	995		Lime, anhy, broken shale
995	1015		Anhy
1015	1060		Lime shells and red
1060	1085		Anhy and red
1085	1155		Lime, red shale, anhy
1155	1700		Anhy
1700	1730		Red shale and lime
1730	2165		Anhy
2165	2170		Gray sandy shale
2170	2310		Anhy, red bed
2310	2450		Lime
2450	2455		Sandy shale--show of gas and oil
2455	2638		Lime
2638			Total depth