

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well  gas well  other P&A

2. NAME OF OPERATOR  
Dixon & Yates Oil Company/

3. ADDRESS OF OPERATOR  
207 So. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660 FNL & 660 FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

AUG 27 1982

O.C.D.

ARTESIA OFFICE

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON\*

(other)

SUBSEQUENT REPORT

RECEIVED

AUG 20 1982

OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO

5. LEASE LC-055696

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Boulter

9. WELL NO.  
3

10. FIELD OR WILDCAT NAME  
Loco Hills Q-G-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit D, Sec. 14-18S-29E

12. COUNTY OR PARISH Eddy

13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3505 GR

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to plug and abandon this well as follows:

- Set CIBP at 2500' & cap w/35' Class C cement.
- Perforate at 1200' and pump 35 sacks Class C cement behind 4 1/2" pipe & leave 100' of cement inside 4 1/2" pipe.
- Perforate at ~~100'~~ <sup>420'</sup> and pump 35 sacks Class C cement behind 4 1/2" pipe & leave 100' of cement inside 4 1/2" pipe.
- Place 50' plug at surface with regulation abandonment marker.
- Surface will be restored in accordance with Minerals Management Services requirements.
- Verbal approval for plugging procedure obtained from Mr. Peter Chester, MMS, Roswell, on 8-18-82.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Lybenta Doodlett TITLE Engineering Secty DATE 8-18-82

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

AUG 26 1982

FOR  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

See Instructions on Reverse Side