

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 6852

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "EA"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Empire Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 12, T-18-S, R-27-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER **RECEIVED**

2. NAME OF OPERATOR
Robert G. Cox ✓ **JUL 30 1973**

3. ADDRESS OF OPERATOR
6222 North Central Expy., Dallas, Texas 75206

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface **455**
330' FNL & 425' FWL of Sec. 12, T-18-S, R-27-E, Eddy County, New Mexico
U. S. G. S. ARTESIA, OFFICE

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3609' GR, 3620' RT

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. MI & RU Casing Pulling Unit about July 27, 1973.
2. Run tubing and spot cement plug from PSTD @ 6195' to 6095' (Perforations at 6165' - 6184'.)
3. Cut off casing at approximately 5200' (Calculated top cement @ 5790') and pull casing.
4. Set 100' cement plug in and out of casing stub.
5. Set 100' cement plug at approximately 2700' - 2800'.
6. Set 100' cement plug in and out of bottom of 8 5/8" surface pipe (14-97') @ 1447' - 1547'.
7. Set 20 sacks cement plug @ surface.
8. Place cap and appropriate marker on well.

Note: Notification by telephone will be given prior to setting plugs in the event U. S. G. S. personnel may want to witness same.

RECEIVED
JUL 23 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Robert G. Cox TITLE Operator DATE 7/19/73

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE DISTRICT ENGINEER DATE JUL 25 1973

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.