

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Ralph Nit</u>		Lease <u>Lynn</u>			Well # <u>1</u>
Location of Well	Unit <u>F</u>	Section <u>26</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Salazar Bros. Inc.</u>		Type of Equipment <u>Rotary</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	<u>8 5/8</u>	<u>24 #</u>		<u>910</u>	<u>525 Gcs</u>
<u>6 1/4</u>	<u>4 1/2</u>	<u>10.5 #</u>		<u>TD</u>	<u>375</u>

Casing Data:

Surface            joints of 8 5/8" inch 24 # Grade J-55  
(Approved) (Rejected)

Inspected by MoSo date 7/12/82

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required           

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 920' Set 920' Feet of 8 5/8" Inch 24 # Grade J-55

New-used csg. @ 920' with 200 sacks neat cement around shoe  
 + 300 sax 17/4 additives (6 # gels, 1/4 # floes, 3% cc)

Plug down @ 3:00 (AM)  (PM) Date 7/14/82

Cement circulated Yes No. of Sacks 75

Cemented by Hullinton Witnessed by Mike Stubblefield

Temp. Survey ran @            (AM) (PM) Date            top cement @           

Casing test @            (AM) (PM) Date           

Method Used            Witnessed by           

Checked for shut off @            (AM) (PM) Date           

Method used            Witnessed by           

Remarks:           

No centralizers

Full returns to TD

last dip level @ 812'

