

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

2157
Op

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-015-31649
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-5867
7. Lease Name or Unit Agreement Name Tumbledink AVK State Com
8. Well No. 2
9. Pool name or Wildcat Richard Knob Atoka Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3543' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line
Section 16 Township 18S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Spud, conductor, resume drilling, surface casing & cement</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 12:00 noon 4-23-2001. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Gerry Guy w/OCD-Artesia via voice mail. Resumed drilling a 17-1/2" hole at 10:30 PM 5-1-2001.

TD 400'. Reached TD at 5:45 AM 5-2-2001. Ran 9 joints of 13-3/8" 48# H-40 8rd ST&C (406.20') of casing set at 400'. 1-Texas Pattern notched guide shoe set at 400'. Insert float set at 360'. Cemented with 400 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 11:00 AM 5-2-2001. Bumped plug to 420 psi, OK. Circulated 10 sacks cement. WOC. Cut off and welded on flow nipple. Drilled out at 6:45 AM 5-3-2001. WOC 19 hours and 45 minutes. Reduced hole to 12-1/4". Resumed drilling. NOTE: Notified Bryan w/OCD-Artesia of operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 30, 2001

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

NOV 13 2001