


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico




WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

National Associated Petr. Co.

Forest H. Lindsey, 502 Ritz Bldg.

Tulsa, Oklahoma

Company or Operator

Address

Forest 1227 Well No. in NW of Sec. 12, T. 19 S.

R. 26 E N. M. P. M. Artesian Basin Field, Bddy County.

Well is 2970 feet south of the North line and 3630 feet west of the East line of Sec. 12-19-26

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Forest Lee Address Artesia, New Mexico

If Government land the permittee is Address

The Lessee is Forest H. Lindsey Address Tulsa, Oklahoma

Drilling commenced 1-10 1945 Drilling was completed 3-22 1945

Name of drilling contractor Fred Peal Address Artesia, New Mexico

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	40	8	Std.	700'	reg.				shot off
8"	28	8	"	1152'	"				curve

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12	10	700	90	Haliberton		
10	8"	1152	75	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 1 feet to 2202 feet, and from feet to feet

PRODUCTION

Put to producing Dry 19

The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Geo Pennington Driller A. H. Christmas Driller

F. A. Johnson Driller N. P. Willis Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 24th

day of March 19 45

Notary Public

My Commission expires 9/15/1948

Artesia, New Mexico 3-24-45

Name H. H. Postle

Position Geol Engnr

Representing Forest H. Lindsey Company or Operator

Address Tulsa Oklahoma

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
1	10	10	Soil
10	21	11	Red Shale
21	30	9	Sand & Gravel - Water
30	47	17	Water Sand
47	65	18	Red Bed
65	80	15	Water Sand
80	92	12	Brown Shale
92	152	60	Red Shale
152	178	26	White Shale & Gravel
178	185	7	Water Sand
185	220	35	Gyp
220	228	8	Lime
228	245	17	Sand & Gravel
245	265	20	Brown Shale
265	320	55	Anhydrite
320	350	30	" Broken
350	373	23	Anhydrite
373	385	12	Red Shale
385	499	110	Anhydrite
495	520	25	" & Shale
520	565	45	Lime
565	588	23	Lime
588	603	15	Red Shale
603	610	7	Anhydrite
610	630	20	Sandy Lime
630	655	25	Sand
655	700	45	Anhydrite set 700' of 10" cemented 50 Sks.
700	715	15	Drilling plug
715	735	20	Red Sand
735	795	60	Lime
795	805	10	Red Shale
805	810	5	Anhydrite
810	840	30	Lime
840	870	30	Anhydrite
870	935	65	Sand
935	940	5	Sand & Water
940	955	15	Red Sand Hard
955	975	20	Sandy Lime
975	985	10	Red Sand (Hard)
985	1058	73	Lime
1058	1060	2	Blue Shale
1060	1070	10	Lime & Sand
1070	1152	82	Lime Set 1152' of 8" with 75 sks.
1152	1240	88	Lime
1240	1255	15	Broken Lime
1255	1400	145	Lime
1400	1410	10	White Lime
1410	1675	265	Lime
1675	1685	10	White Lime
1685	2002	317	Lime
2002			Total Depth