

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Robert E. Meloe, General Contractor, Inc.

(Company or Operator)

State ✓

(Lease)

Well No. 15 ✓, in NW ✓ ¼ of SE ¼, of Sec. 3 ✓, T. 19, R. 29, NMPM.

Turkey Track ✓

Pool,

1047

County.

Well is 1980' ✓ feet from South line and 1850' ✓ feet from East line of Section 3. If State Land the Oil and Gas Lease No. is.

Drilling Commenced May 19, 1955 Drilling was Completed July 24, 1955

Name of Drilling Contractor Owner

Address P. O. Box 246 Artesia, New Mexico

Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until, 19.

OIL SANDS OR ZONES

No. 1, from 1539 to 1551	No. 4, from to
No. 2, from 1776 to 1780	No. 5, from to
No. 3, from 2160 to 2175	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to	feet.
No. 2, from to	feet.
No. 3, from to	feet.
No. 4, from to	feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	New	312	Regular			
7"	20	1/2 New	2155	"			
5 1/2"	15	New	2162	"	Will cut and pull at approximately 1700'		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 5/8	312'	20	Denton		
8"	7"	2155'	25	Denton		
7"		Squeezed hole in casing at 1112' with 25 sacks				
5 1/2"		2161	31	Denton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.

Depth Cleaned Out.

CORD OF DRILL-STEM AND SPECIAL TF

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto:

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing....., 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	70	70	Caliche	1075	1130	55	Anhy. and Lime
70	90	20	Red Rock	1130	1240	110	Anhy.
90	180	90	Anhy.	1240	1525	285	Anhy Broken
180	190	10	Red Shale	1525	1539	14	Anhy.
190	215	25	Anhy.	1539	1551	12	Sand
215	230	15	Red Shale	1551	1600	49	Anhy.
230	250	20	Anhy.	1600	1605	5	Lime and Anhy. Hard
250	260	10	Blue Shale	1605	1730	125	Lime
260	270	10	Anhy.	1730	1755	25	White Lime
270	295	25	Broken Anhy.	1755	1899	144	Lime
295	380	85	Salt	1899	1920	21	Lime Hard
380	465	85	Salt & Red Shale	1920	1942	22	Lime
465	675	210	Salt	1942	1959	17	Gray Lime - Hard
675	720	45	Anhy. and Salt	1959	1978	19	Lime
720	791	71	Salt	1978	2053	75	Lime
791	830	39	Anhy. Hard	2053	2079	26	Lime Broken
830	970	140	Broken Anhy. and Salt	2079	2127	48	Lime
970	1070	100	Anhy.	2127	2140	13	Anhy. and Lime
1070	1075	5	Lime	2140	2164	24	Lime
				2164	2175	11	Sand T.D.

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 8, 1955

(Date)

Company or Operator.....Address.....

Name.....Position or Title.....