

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD


AREA 640 ACRES  
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

Henry Swift San Antonio, Texas  
Company or Operator Address  
State Well No. 1 in NW NE of Sec. 30, T. 19  
Lease  
R. 29 N. M. P. M. Wildcat Field, Eddy County.  
Well is 680 feet south of the North line and 1995 feet west of the East line of section 20  
If State land the oil and gas lease is No. B-256 Assignment No.  
If patented land the owner is Address  
If Government land the permittee is Address  
The Lessee is Henry Swift Address San Antonio, Texas  
Drilling commenced October 22 1939 Drilling was completed December 6 1939  
Name of drilling contractor Jamison & Pollard Address Abilene, Texas  
Elevation above sea level at top of casing 3805 feet.  
The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from to No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 680 to 280 feet. Hole full of water  
No. 2, from 1520 to 1605 feet. 4 BWPH  
No. 3, from 2208 to 2215 feet. Hole full subphur water  
No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	40#	8thd	Nat'l	33'					Surface
3 1/2"	28#	8thd	Nat'l	417'					Water S.O.

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2"	417'	50	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet  
Cable tools were used from 0 feet to 2215 feet, and from feet to feet

## PRODUCTION

Put to producing Well not productive 19  
The production of the first 24 hours was barrels of fluid of which % was oil; %  
emulsion; % water; and % sediment. Gravity, Be  
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas  
Rock pressure, lbs. per sq. in.

## EMPLOYEES

H. T. Marshall Driller J. W. Miller Driller  
Reese Porter Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11

Hobbs, New Mexico 1-11-40  
Place Date

day of January 1940

Name C. C. Rollard

SEAL

Position Drilling Contractor

Norma Belle

Representing Henry Swift  
Company or Operator

Notary Public

My Commission expires November 20, 1943

Address San Antonio, Texas

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	70		Sand
70	85		Gravel
85	90		Anhy
90	115		Sand
115	137		Anhy & sand
137	140		Red rock and anhy
140	160		Anhy, hole full water
160	180		Salt, anhy, potash.
180	193		Salt, anhy, potash
193	198		Anhy
198	203		Salt
203	210		Lime
210	210		Red rock
210	2170		Lime
2170	2193		Anhy and red rock
2193	2198		Lime and anhy
2198	2209		Anhy
2209	2233		Lime and anhy
2233	2234		Sand and anhy
2234	2271		Anhy
2271	2283		Sandy shale & anhy
2283	2271		Lime
2271	2297		Sandy shale
2297	2340		Lime
2340	2378		Sand
2378	2439		Lime
2439	2442		Sand smell of sulphur & rainbow oil
2442	2446		Lime
2446			Total depth