



NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Kincaid & Watson Drilling Company  
(Company or Operator)

Gulf State  
(Lease)

Well No. 1, in SE 1/4 of SW 1/4, of Sec. 16, T. 19S, R. 31E, NMPM.

Undesignated Pool, Eddy County.

Well is 660 feet from South line and 1980 feet from West line

of Section 16-19-31. If State Land the Oil and Gas Lease No. is E-6273

Drilling Commenced 4-25-62, 19... Drilling was Completed 5-15-62, 19...

Name of Drilling Contractor Kincaid & Watson Drilling Company

Address P.O. Box 498, Artesia, New Mexico

Elevation above sea level at Top of Tubing Head GL 3491. The information given is to be kept confidential until 19...

OIL SANDS OR ZONES

No. 1, from Slight 2370 to 2381 No. 4, from...  
No. 2, from... to... No. 5, from... to...  
No. 3, from... to... No. 6, from... to...

RECEIVED  
MAY 29 1962

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 455-60 to... feet.  
No. 2, from 565-75 to... feet.  
No. 3, from 585-95 to... feet.  
No. 4, from 2465-79 to... feet.

O. C. C.  
ARTESIA, OFFICE

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8"	24	Used	717.68	Reg.	80	None	Surface

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	8 5/8"	717.68	50	Denton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation...  
Depth Cleaned Out...

# RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.  
Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

## PRODUCTION

Put to Producing....., 19.....  
Plugged & abandoned....., 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was  
was oil; .....% was emulsion; .....% water; and.....% was sediment. A.P.I.  
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of  
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy.....	410	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	705	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	1965	T. Montoya.....	T. Farmington.....
T. Yates.....	2370	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	2465	T. McKee.....	T. Menefee.....
T. Queen.....		T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....		T. Gr. Wash.....	T. Mancos.....
T. San Andres.....		T. Granite.....	T. Dakota.....
T. Glorieta.....		T. ....	T. Morrison.....
T. Drinkard.....		T. ....	T. Penn.....
T. Tubbs.....		T. ....	T. ....
T. Abo.....		T. ....	T. ....
T. Penn.....		T. ....	T. ....
T. Miss.....		T. ....	T. ....

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	10	10	Caliche	2370	2381	11	Sand
10	410	400	Sand & red bed	2381	2395	14	Lime
410	440	30	Anhydrite	2395	2455	60	Sandy lime
440	455	15	Red shale	2455	2465	10	Anhydrite & lime
455	460	5	Sand	2465	2479	14	Lime & sand
460	545	85	Anhydrite	2479	TD		
545	553	8	Red shale				
553	565	12	Anhydrite				
565	575	10	Water sand				
575	585	10	Red shale				
585	595	10	Sand				
595	685	90	Red bed & red rock				
685	705	20	Anhydrite				
705	1965	1260	Salt				
1965	2154	189	Anhydrite				
2154	2162	8	Lime				
2162	2182	20	Anhydrite				
2182	2220	38	Anhydrite & sand				
2220	2230	10	Anhydrite				
2230	2265	35	Anhydrite & shale				
2265	2310	45	Sandy shale				
2310	2343	33	Anhydrite & lime				
2343	2350	7	Gray lime				
2350	2355	5	White lime				
2355	2370	15	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

*G. Rex Holmes* May 29, 1963  
(Date)

Company or Operator.....Kincaid & Watson Drilling Co.

Address.....Box 498, Artesia, New Mexico

Name.....G. Rex Holmes

Position or Title.....Assistant Secretary