Form 9-331 a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

Form Approved.

Land Office

Unit Mallet Federal

SHOOK FRICT ENGINEER

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

301	DKI NOI			
NOTICE OF INTENTION TO	DRILL		SUBSEQUENT REPORT OF WATER SHUT	Г-OFF
NOTICE OF INTENTION TO	O CHANGE PLANS	S	SUBSEQUENT REPORT OF SHOOTING O	R ACIDIZING
NOTICE OF INTENTION TO	O TEST WATER SHUT-OF	F 8	SUBSEQUENT REPORT OF ALTERING C	ASING
NOTICE OF INTENTION TO	O RE-DRILL OR REPAIR	WELL	SUBSEQUENT REPORT OF RE-DRILLING	OR REPAIR
NOTICE OF INTENTION TO	O SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONME	NT
NOTICE OF INTENTION TO	O PULL OR ALTER CASIF	NG	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO	O ABANDON WELL		Liew to transcradada	*
nglish Federa		Y CHECK MARK NATUR	E OF REPORT, NOTICE, OR OTHER DAT.	A)
			10/7/63	, 19 . .
	is located 66	o ft. from	line and 1980 ft. from	w line of sec.
// of /// of (½ Sec. and Sec. No	.) (T	wp.) (Range)	(Meridian)	•
North Backbe		BAAY	New M	exico
(Field)		(County or Subdi	vision) (Sta	te or Territory)
ate names of and expect	ed depths to objective s ing p	DETAILS (sands; show sizes, weigoints, and all other in	ghts, and lengths of proposed casings apportant proposed work)	4
ate names of and expect ginning 10-3- lotted 50° cms 1250° and 10 lotted 100° cm lotted 100° cm lotted 50° plu	ed depths to objective s ingp 63 and ending ont plug 2100 50' - resover ment plug - 5 ment plug - 5	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050' Pull ed 1061.58' in and 50 in and 50 5/8" casing	of WORK this, and lengths of proposed casings apportant proposed work) a 2" tubing, displace led tubing, welded on 5 1/2" casing. Remind of 5 1/2" casing with 4" parker, 6' i	d hole w/md, 5 1/2" casing, s tubing to 1050'. g = 1000-1100'. g = 530-650'.
eate names of and expect ligitating 10-3- notted 50° cent to 1250° and 10 notted 100° cented 100° cented 100° cented 50° plu	ed depths to objective s ingp 63 and ending ont plug 2100 50' - resover ment plug - 5 ment plug - 5	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050' Pull ed 1061.58' in and 50 in and 50 5/8" casing	of WORK this, and lengths of proposed casings apportant proposed work) a 2" tubing, displace led tubing, welded on 5 1/2" casing. Remind of 5 1/2" casing with 4" parker, 6' i	d hole w/md, 5 1/2" casing, s tubing to 1050". g = 1000-1100". g = 530-650".
eginning 10-3- notted 50° cm 1250° and 10 notted 100° cm notted 100° cm notted 50° plu bove ground.	ed depths to objective s ing p 63 and ording ent plug 2100 50' - recover ment plug - 5 ment plug - 5 g in top of 8	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050'. Pull ed 1061.58' in and 50 of in and 50 5/8" casing RECE	of Work This, and lengths of proposed casings apportant proposed work) The staking, displace led taking, welded on 1/2" easing. Ber out of 5 1/2" casin out of 5 1/2" casin with 4" marker, 6' 1 VED 3 1964	d hole w/md, 5 1/2" casing, s tubing to 1050'. g = 1000-1100'. g = 530-650'.
ate names of and expect ginning 10-3- cotted 50° cess : 1250° and 10 cotted 100° ce cotted 100° ce cotted 50° plus cove ground.	ed depths to objective s ing p 63 and ording ent plug 2100 50' - recover ment plug - 5 ment plug - 5 g in top of 8	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050'. Pull ed 1061.58' in and 50 of in and 50 5/8" casing RECE	of Work This, and lengths of proposed casings apportant proposed work) The staking, displace led taking, welded on 1/2" easing. Ber out of 5 1/2" casin out of 5 1/2" casin with 4" marker, 6' 1 VED 3 1964	d hole w/md, 5 1/2 casing, s tubing to 1050. g - 1000-1100. g - 530-690. n cases and A'
rate names of and expect Defining 10-3- Dotted 50° can 1250° and 10 Dotted 100° can Dotted 100° can Dotted 50° plus Dove grounds I understand that this Ompany	ed depths to objective s ing p 63 and ording ent plug 2100 50' - recover ment plug - 5 ment plug - 5 g in top of 8	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050'. Pull ed 1061.58' in and 50 of in and 50 5/8" casing RECE	of Work This, and lengths of proposed casings apportant proposed work) The staking, displace led taking, welded on 1/2" easing. Ber out of 5 1/2" casin out of 5 1/2" casin with 4" marker, 6' 1 VED 3 1964	d hole w/md, 5 1/2" casing, s tubing to 1050'. g - 1000-1100'. g - 530-690'. n casest and A'
ginning 10-3- botted 50° cess 1250° and 10 cetted 100° ce cotted 100° ce cotted 50° plus cove grounds	ed depths to objective so ing p 63 and ording ent plug 2100 50' - resover ment plug - 5 ment plug - 5 g in top of 8 plan of work must rece 611 Company	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050'. Pull ed 1061.58' in and 50 of in and 50 5/8" casing RECE	of WORK The state of proposed casings apprent proposed work) The state of proposed casings apprent proposed work) The state of the s	d hole w/md, 5 1/2 can ng, s tubing to 1050 . g - 1000-1100 . g - 530-650 . n oscass and 4'
ate names of and expect lightning 10-3- lotted 50° ces lightning 10-3- lotted 50° ces lotted 100° ce lotted 50° plus love ground. I understand that this lompany	ed depths to objective a ing p 63 and exiting ent plug 2100 50' - resever ment plug - 5 ment plug - 5 g in top of 8 plan of work must rece 611 Company	DETAILS (sands; show sizes, weigoints, and all other in 10-4-63, res 2050'. Pull ed 1061.58' in and 50 of in and 50 5/8" casing RECE	of WORK white, and lengths of proposed casings apportant proposed work) a 2" tubing, displace led tubing, wolded on the first of 5 1/2" casing. out of 5 1/2" casing. out of 8 5/8" casing with 4" carrier, 6' i	d hole w/md, 5 1/2 can ng, s tubing to 1050 . g - 1000-1100 . g - 530-650 . n oscass and 4'