

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

MAR 29 1967

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Re-entry	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Thomas
3. Address of Operator 309 Carper Building	9. Well No. 1
4. Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM East 8 19S 25E THE LINE, SECTION TOWNSHIP RANGE NMPM.	10. Field and Pool, or Wildcat Penasco Draw S.A. Yes
15. Elevation (Show whether DF, RT, GR, etc.) 3541 GL 3552 KB	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Sand Frac & Perforate <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-16-17-67 - This well was perforated and Sand Frac using Otis bridge plugs as follows:
Perforated: 60/2465-2525'; 30/2155-2180'; 20/2180-2190'; 10/2190-2200'; 15/1482-1500'; 20/1320-1370'. **
Sand Frac down casing thru open hole from 2900-2954' with 40,000# 20-40 sd and 1428 bbls of water. Set bridge plug 2525-2900' and Sand Frac from 2465-2525' with 40,000# sd (20-40) and 1476 bbls water. Set bridge plug 2200-2425' and Sand Frac from 2155-2180; 2180-2190; 2190-2200' with 40,000# 20-40 sd and 1364 bbls water. Set bridge plug 1500-2155' and Sand Frac 1482-1500' 1320-1370' with 20,000# 20-40 sand and 1302 bbls water. Recovered bridge plugs and installed pumping equipment.
Total Sand: 140,000# - Total Water 5570 barrels.

** - Depths measured from Kelly Bushing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Richard C. Norman</u>	TITLE <u>Geologist</u>	DATE <u>3-29-67</u>
APPROVED BY <u>W. A. Gussert</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>MAR 30 1967</u>

CONDITIONS OF APPROVAL, IF ANY: