

Form 9-231a  
(7-57)

APPROVED

JUN 13 1963  
RONNIE E. SHOOK  
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office New Mexico  
Lease No. 0107697  
Unit K

RECEIVED

JUN 14 1963

## SUNDRY NOTICES AND REPORTS ON WELLS

D. C. C.

ARTESIA, OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 7, 1963

**Jones** ✓  
Well No. 1-23 is located 1650 ft. from N line and 1650 ft. from W line of sec. 23  
NE/4 SW/4 198 31E NMPM  
( $\frac{1}{4}$  Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildcat Edley New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ..... ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 17½" hole to 525'. Set 514' of 13-3/8" 48½ E-40 casing, cemented with 500 sac Incon with 2% NA-5. Plug down 10:40 AM, MST, 5-25-63.

Drilled 11" hole to 4000'. Set 4000' of 8-5/8" J-95 32½ and 24½ casing in two stages. Cemented first stage with 150 sac Incon Pozmix with 6% Gel and 2% calcium chloride and 2½ gilsonite per sack followed by 100 sac Incon Heat with 2% calcium chloride. Cemented second stage with 1900 sac Incon 6% Gel 2% calcium chloride with 16½ salt per sack followed with 100 sac Incon Heat with 16½ salt per sack and 2% calcium chloride. Plug down 8:00 AM, MST, 6-4-63. Tested okay.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company DELNI-TAYLOR OIL CORPORATIONAddress P. O. Box 1821Midland, TexasBy [Signature]Title District Clerk