

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office New MexicoLease No. 0107697Unit XRECEIVED
NOV 8 1963D. C. C.
ARTERIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 4, 1963

Jones

Well No. 1-23 is located 1650 ft. from XXX line and 1650 ft. from YEX line of sec. 23NE 1/4 SW 1/4
(1/4 Sec. and Sec. No.)196
(Twp.)31E
(Range)NMPM
(Meridian)Black Stream (Undesignated)
(Field)Edgy
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 3559 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

TD 12,853'. PWD 12,365'. Set Baker cast iron bridge plug at 12,365'. Perforated Stream 11,174-82', 11,186-94', 11,212-19', 11,232-36', 11,292-97', 11,308-88', 11,357-64', 11,368-76', 11,466-70', 11,484-507' with 2 JEFF. Acidized with 1500 gallons breakdown acid. Tested. Set Halliburton cement retainer at 11,273'. Squashed lower Stream perfs below 11,273' with 50 sacks Trinity Inferno cement. PWD 11,273'. Acidized with 10,000 gallons Dowell XF acid. Swabbed and flowed back acid with trace of oil. Acid fraced with 100,000 gallons 7-1/2% acid. First 50,000 gallons 50¢ per 1000 gallons of N-33 and 50¢ per 1000 of FLAX-2. Second 50,000 gallons 50¢ per 1000 of N-33 and 29,000¢ of 20-40 sand. Flowed and swabbed acid water and oil. Testing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company DELHI-TAYLOR OIL CORPORATIONAddress P. O. Box 1521Midland, TexasBy S. MitchellTitle District Clerk