

## WELL PROFILE

OPERATOR Shenandoah Oil Corp.

CASING

LINER

1

2

3

WELL # Shugart D-9FIELD ShugartCOUNTY EddySTATE New MexicoDATE 3/16/70☐ NEW COMPLETION☒ WORKOVER

Waterflood

SIZE

WEIGHT

GRADE

THREAD

DEPTH

ITEM  
NO.

EQUIPMENT AND SERVICES

ESTIMATE

Above top packer (113 lbs. Total in well)  
Subs under top Joint (Subs = 8', 6', 6', 4', 2')3337' size 45-B Baker Model "B" Tandem Tension Packer  
w/unloader (602-21-2146) w/TK-69 plastic internally  
and externally.3373' size 2-3/8 X 4' Baker Model "BF" Full Opening  
Down Hole Flow Regulator (600-34-2005) w/TK-69  
plastic internally and externally.  
(monel piston)3674' size 45-B Baker Model "A-2" Lok-Set Retrievable  
Casing Packer (646-12-2149) w/TK-69 plastic  
internally and externally.3711' size 2-3/8 X 4' Baker Model "BF" Full Opening  
Down Hole Flow Regulator (600-34-2005) w/TK-69  
plastic internally and externally.  
(monel piston)

3782' Tubing T.D.

3800' Present well T.D.

COMMENTS:

TOTAL ESTIMATE

Packer set in 15,000# tension.

Fluid in well when packers run approx. 3200'.

Zero is 2' above ground level.

Slip type wellhead.

Shenandoah Repr. --- C.W. Downey, Hobbs, N.M.

Pat Bates, Ft. Worth, Texas

PREPARED BY

M.R. Kruschke, Sr.

OFFICE

Odessa, Texas

PHONE

915-337-2383

Regional Staff Tech.

Worksheet  
No. 523SAVE TIME AND MONEY WITH  
COMPLETIONS BY BAKER**BAKER OIL TOOLS, INC.**

HOUSTON LOS ANGELES NEW YORK

WELL INITIAL  
FLUIDS FINAL

PRINTED IN U.S.A.

Office size &  
b/d:  
Equipment &  
Tubing Tally:

5 1/2"  
14 1/2"/15.5"

2 3/4" C.W. S-R.  
Plastic Int.

100 lbs.  
+  
26' Subs

3335.61'

3.05'

3330'

4.11'

1820'  
300  
b/d

296.91'

3.55'

3225'

4.11'

3250'

3250'

.75'

19/64  
240  
b/d  
Total

B.P.

**RECEIVED**

APR 6 - 1970

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO