



| FROM- | TO- | TOTAL FEET | FORMATION |
|-------|-----|------------|-----------|
|       |     |            | Any       |
|       |     |            | Base Salt |
|       |     |            | Queen     |
|       |     |            | Penrose   |
|       |     |            | Tp Salt   |
|       |     |            | Yates     |
|       |     |            | 840       |
|       |     |            | 2415      |
|       |     |            | 3499      |

FORMATION RECORD—continued

| FROM- | TO- | TOTAL FEET | FORMATION |
|-------|-----|------------|-----------|
|       |     |            | Any       |
|       |     |            | Base Salt |
|       |     |            | Queen     |
|       |     |            | Penrose   |
|       |     |            | Tp Salt   |
|       |     |            | Yates     |
|       |     |            | 840       |
|       |     |            | 2415      |
|       |     |            | 3499      |

U. S. GOVERNMENT PRINTING OFFICE 16-43094-2

HISTORY OF OIL OR GAS WELL

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

CASING RECORD

Spud date 9/29/63. Drilled 10" hole to 883', and ran 19 1/2 20# casing in w/50 sx reg neat cement. 31st cement set, ran bailer and cleaned out annulus. Matted 1 hour and ran bailer and well bailed dry. Drilled ahead making 8" hole.

Drilled to total depth of 3842', and ran surveys. Well dry. Plugging application filed 11/19/63 and approved 11/26/63 for permanent abandonment. Plugging was performed and lease cleared of all equipment, location and pits were returned to original contour, and permanent marker set to identify the location.

Completed drilling. Drilled 10" hole to 883', and ran 19 1/2 20# casing in w/50 sx reg neat cement. 31st cement set, ran bailer and cleaned out annulus. Matted 1 hour and ran bailer and well bailed dry. Drilled ahead making 8" hole.

Drilled to total depth of 3842', and ran surveys. Well dry. Plugging application filed 11/19/63 and approved 11/26/63 for permanent abandonment. Plugging was performed and lease cleared of all equipment, location and pits were returned to original contour, and permanent marker set to identify the location.

Completed drilling. Drilled 10" hole to 883', and ran 19 1/2 20# casing in w/50 sx reg neat cement. 31st cement set, ran bailer and cleaned out annulus. Matted 1 hour and ran bailer and well bailed dry. Drilled ahead making 8" hole.

Drilled to total depth of 3842', and ran surveys. Well dry. Plugging application filed 11/19/63 and approved 11/26/63 for permanent abandonment. Plugging was performed and lease cleared of all equipment, location and pits were returned to original contour, and permanent marker set to identify the location.

Completed drilling. Drilled 10" hole to 883', and ran 19 1/2 20# casing in w/50 sx reg neat cement. 31st cement set, ran bailer and cleaned out annulus. Matted 1 hour and ran bailer and well bailed dry. Drilled ahead making 8" hole.