

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No. **W-06766**

Unit

copy to 27.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	XX
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 25, 1964

Federal Holder "CR"
Well No. **14** is located **2310** ft. from **[N]** line and **990** ft. from **[E]** line of sec. **24**
SE/4, NE/4, Sec 24 **19-8** **30-E** **NMPN**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
North Hackberry Yates **Edgar** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3416** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

2125' TD, 2072' FB.

Loaded hole with oil and spotted 250 gallons of 15% HCl acid. Perforated 4-1/2" casing at 2096-2098' with 4 JH. Freed as follows: Spearhead with 1500 gallons of gelled oil with 1/400 Adomite M-11, 3000 gallons of gelled oil with 1/400 Adomite M-11 and 2# 20-40 sand per gallon, 1000 gallons of gelled oil with 1/400 Adomite M-11 and 2# 10-20 SPG. Flushed with 36 barrels of oil. Maximum pressure 2800#, Minimum pressure 1800#. AIR 8 bpm. Soaked dry. Ran GI cement retainer and set at 2082'. Squeezed perforations 2096-2098' with 150 sacks of Class "A" Neat cement. Max. Press. 3800#, Perforated 4-1/2" casing 2022-2024' and 2048-50' with 4 jet holes. Freed as follows: Spearhead with 1500 gallons of gelled oil with 1/400 Adomite M-11 per gallon, 3000 gallons of gelled oil with 1/400 Adomite M-11 and 2# 20-40 SPG, 1000 gallons of gelled oil with 1/400 Adomite M-11 and 2# 10-20 SPG. Dropped 4, 1-1/4" RMB sealers. Pressure increased 800#. Spearhead with 1500 gallons of gelled oil with (See Attachment)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Gulf Oil Corporation**Address **Box 670****Hobbs, New Mexico**

RECEIVED

DEC 1 1964

By

Area Petroleum Engineer

M. O. C. C.

ARTESIA, OFFICE

Attachment, 9-331 a, Gulf Oil Corporation, Federal Holder "CR" No. 10, Section 24
19-S, 30-E, Midy County, New Mexico.

1/40# Adomite M-11, 3000 gallons gelled oil with 1/40# Adomite M-11 and 2# 20-40
SPG, 1000 gallons gelled oil with 1/40# Adomite M-11 and 2# 10-20 SPG. Flushed
with 36 barrels of oil. Maximum pressure 3500#, Minimum pressure 2400#. AIR 18
bpm. Scrubbed and cleaned up. Ran 2-3/8" tubing with bull plug on bottom, set
at 2060', 2# at 2044'. Ran rods and pump and placed well on production.

RECEIVED

DEC 1 1964

C. G. P.
ARTERIA, OFFICE