

30-015-10357

Rec'd. 4-8-65

1-Induction Electrolog

Rec'd. 4-16-65

1 Acoustilog

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210
FORM APPROVED
Budget Form No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Phillips Petroleum Company

3. Address and Telephone No.
4001 Penbrook Street, Odessa, TX 79762

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit O, 660' FSL & 1980' FWL of Section 13, T-19-S,
R-31-E

5. Lease Designation and Serial No.

NM 05470C

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Simon "A" No. 1

9. API Well No.

30-015-10357

10. Field and Pool, or Exploratory Area

Lusk (Strawn)

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8-17-94 Plug #1 Spot 65 sxs Class H cmt. 15.6# gal @6015'. Tagged TOC @5814'.
8-18-94 Plug #2 Spot 70 sxs Class H cmt. 15.6# gal @5260'. Tagged TOC @5032'.
8-18-94 Plug #3 Spot 70 sxs Class H cmt. 15.6# gal @4094'. Tagged TOC @3991'.
8-18-94 Plug #4 Spot 30 sxs Class C cmt. 14.8# gal - from 3991' to 3881'.
8-18-94 Plug #5 Spot 65 sxs Class C cmt. 14.8# gal - From 2606' to 2366'.
Tagged @2570'.
8-19-94 Plug #6 Spot 65 sxs Class C cmt. 14.8# gal @2570'. Tagged TOC @2333'.
8-19-94 Plug #7 Perforated 8-5/8" csg. @775'. Set 8-5/8" pkr. @500'. Squeezed
130 sx Class C cmt under pkr & displaced TOC to 600'. Tagged
TOC @582'.
8-19-94 Plug #8 Perforated 8-5/8" csg. @100'. Pumped 70 sxs Class H cmt. 15.6#
gal cmt. down 8-5/8" & circ. cmt. to surface on 8-5/8"x13-3/8"
annulus. Left cmt. @ surface on 8-5/8" inside.

P&A 8-19-94

Approved as to plugging of the well bore
Lucky under bond is retained until
surface restoration is completed

14. I hereby certify that the foregoing is true and correct

Signed

Title Supv. Regulatory Affairs

Date 9-13-94

(This space for Federal or State office use)

M. Sanders

(915) 368-1488

Approved by

(ORIG. SGD.) JOE G. LARA

Title

PETROLEUM ENGINEER

Date 10/19/94

Conditions of approval, if any: