

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210 *CSF*

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NMMN 94845

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Duncan Federal No. 1

9. API Well No.

30-015-10375

10. Field and Pool, or Exploratory Area
Lusk Strawn

11. County or Parish, State

Eddy, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Lynx Petroleum Consultants, Inc.

3. Address and Telephone No.

P.O. Box 1979, Hobbs, NM 88241 505-392-6950

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

760' FNL & 990' FEL
Section 27, T-19S, R-31E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☒ Recompletion

☒ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

EVALUATE BONE SPRINGS INTERVAL

1. Set CIBP @ 9500' with 35' of cement on top.
2. Cut and pull 4 1/2" casing @ 7300'.
3. Spot 25 sxs cement casing stub plug 7250-7350'.
4. Run logs on open hole 7250-3950'.
5. If logs are favorable, run 5 1/2", 15.5# & 17# K-55 casing to 7250' and cement to surface.
6. Perforate, treat, and test Bone Springs intervals 7100-7200'

RECEIVED

OCT 8 1 1995

OIL CON. DIV.
DIST. 2

14. I hereby certify that the foregoing is true and correct

Signed Marc Wise

Title Marc Wise

Date 9/18/95

(This space for Federal or State office use)

Approved by **(ORIG. SCD.) JOE G. LARA**

Title **PETROLEUM ENGINEER**

Date 10/23/95

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side