

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER <u>Drilling Well</u>		5. LEASE DESIGNATION AND SERIAL NO. <u>A-321358</u>
2. NAME OF OPERATOR <u>Southern New Mexico Oil Corp.</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>P. O. Box 1659, Midland, Texas</u>		7. UNIT AGREEMENT NAME <u>Unit Deep</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>1650' from the south line and 590' from the East line of Sec. 24.</u>		8. FARM OR LEASE NAME
14. PERMIT NO.		9. WELL NO. <u>3</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>5551 GR.</u>		10. FIELD AND POOL, OR WILDCAT <u>Unit 511-3</u>
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>NE 1/4 of SE 1/4 of Sec. 24 T-13N, R-31-E</u>
		12. COUNTY OR PARISH <u>Midland</u>
		13. STATE <u>New Mexico</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Test perforating

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11,515' of new 4 1/2" (11.5 and 13.5) # R-40 casing was cemented at 11,521' with 600 sacks of regular plus 200 cu. ft. of stratacrete. Plug was down at 11:45 PM May 30, 1964. After 24 hrs. a pressure of 1500 psi was applied for 30 min. at the surface. There was no pressure loss.

The well was logged and two intervals (11397-11403), (11412-11418) perforated with 2 shots per ft. May 31.

The well will be washed with 1000 gal of mud acid and a potential test made.

RECEIVED

JUN 4 - 1964

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

R. L. BEEHMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

