

NO. OF COPIES RECEIVED		2
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND	FICE	
OPER	OR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

JUL 24 1975

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. NOTE: USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

ARTESIA, OFFICE

1. Indicate Type of Well State <input type="checkbox"/> Rec <input checked="" type="checkbox"/>	
2. State Oil & Gas Lease No.	
3. Name of Operator Yates Petroleum Corporation ✓	
4. Address of Operator 207 South 4th Street - Artesia, NM 88210	
5. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>20</u> RANGE <u>24</u> N.M.P.M.	
6. Elevation (Show whether DF, RT, GP, etc.) 3635' KB	
7. Unit Agreement Name	
8. Name of Lease Holder Foster "AN" Com.	
9. Well No. 1	
10. Field, Foot, or Wildcat Dagger Draw Wolfcamp	
11. County Eddy	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CEMENT <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

Well is presently completed in the Wolfcamp formation at 5750-70 and producing little gas.
Propose to load hole w/water, pull tubing and packer, drill out CIBP and cement at 5740-50', clean hole and set CIBP at approx. 6650' w/2 sacks of cement on top of plug, reperforate Wolfcamp and Selectively test and treat as needed in the following intervals: 6564-69, 6525-31, 6470-76, 6235-39, 6158-64, 5980-88, 5622-28, and 5545-56.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNED <u>Eldon Mayhew</u>	TITLE <u>Engineer</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>
CONDITIONS OF APPROVAL, IF ANY:	
DATE <u>7-23-75</u> <u>JUL 25 1975</u>	