

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN THE ICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

44-05470-C

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Phillips Petroleum Company	8. FARM OR LEASE NAME Simon "A"
3. ADDRESS OF OPERATOR 82 Phillips Bldg. - Odessa, Texas	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface SE 1/4 SE 1/4, 660' FEL, 660' FSL	10. FIELD AND POOL, OR WILDCAT Lusk Strawn
14. PERMIT NO.	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec 14, T19S, R31E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3558' DF	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) * April 12, 1965
Halliburton cemented 8-5/8" (24#) casing at 4000' in two stages. 1st stage with 100 sacks 20% DD followed by 250 sacks Incoor neat. Plug to 3941'. Opened DV tool at 2646'; no cement returns. Stage 2: Cemented thru DV tool with 450 sacks Incoor 40% DD followed by 100 sacks Incoor neat. Closed DV tool with 1500#. Cement did not circulate. WOC 12 hours. Temperature survey top of cement at 1375'. Tested casing with 2400# for 30 minutes, no pressure loss.

RECEIVED

APR 30 1965

C. C. C.
ARTESIA, OFFICE

RECEIVED
APR 29 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Mueller

TITLE

Reservoir Engineer

DATE

4-26-65

(This space for Federal or State office use)

APPROVED BY

APPROVED

TITLE

DATE

APR 29 1965

RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

887-851

