

APPROVED
SUBMIT IN TRIPLICATE
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ACTING DISTRICT ENGINEER GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 02447
Unit Big Eddy

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

PERRY R. BASS - Sun-Tax Federal #1
Well No. 1 is located 660 ft. from S line and 1980 ft. from W line of sec. 27

SW 1/4 Sec. 27
(1/4 Sec. and Sec. No.)

Under
Lusk Strawn
(Flick)

T-19-S R-31-E
(Twp.) (Range)

NMPH
(Meridian)

Eddy
(County) (Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is * Not yet available. ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding and cementing points, and all other important proposed work)

Big West Drilling Co. spudded 20" hole at 7:15 p.m. MST 8-31-65. Drilled 20" hole to 805, finding top Rustler Anhydrite at 780. Set 16" OD 65 #/ft. H-40 ST&C casing with guide shoe and two centralizers on bottom, at 804.07'. Cemented by Halliburton with 750 sx. Trinity Lite-Wate 2% calcium chloride and 200 sx. regular cement 2% calcium chloride. Plug down 10:45 p.m. 9-3-65. Circulated out 320 sx. After WOC 24 hrs., tested casing to 1000 psi for 30 min. Commenced drilling plug at 11:00 p.m. 9-4-65.

Reference is made to the original notice of intention to drill, wherein it was proposed that 11-3/4" OD casing be set at 2600', and recovered after setting 8-5/8" OD casing. It is now proposed that this 11-3/4" OD string be set as planned, but it is to be cemented back to the surface, with no attempt to be made to recover the string. In this way, protection of the salt section is assured. 8-5/8" OD casing will then be cemented back to the base of the 11-3/4" OD casing.

Company PERRY R. BASS

Address Box 1178

Monahans, Texas

By Walter D. Powers
Title Asst. Div. Mgr.

RECEIVED
SEPS 1965
BUREAU OF GEOLOGICAL SURVEY
NEW MEXICO