

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

6. Unit Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. Unit, Oil & Gas Lease No.	E-7256

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER FORMER OR USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Martin Yates, III	8. Farm or Lease Name State N & C
3. Address of Operator 325 Carper Building, Artesia, New Mexico.	9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>Source</u> LINE AND <u>543</u> FEET FROM THE <u>West</u> LINE, SECTION <u>6</u> TOWNSHIP <u>19 S.</u> RANGE <u>29 E.</u> N.M.P.M.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3380 Ground Level	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>Perforating, acidizing & fracturing</u> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On February 2, 1966, squeezed off perforations at 2676' - 2632' with 25 sacks cement. Top of cement plug at 2638'.

Perforated 5½" casing from 2621 - 2625' with 2 Jets per foot and acidized with 1000 gallons regular acid, on February 3. Recovered small amount of oil.

On February 16, 1966, perforated 5½" casing from 2612' - 2613' with 2 jets per foot, and acidized all perforations from 2612' to 2632' with total of 5000 gallons RXI acid and 1000 gallons regular acid. Recovered small amount of oil.

On February 25, 1966, fractured well with 940 barrels Gel water and 50,000# 20-40 sand. Now testing well, on pump, in effort to evaluate reservoir.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gressett TITLE Bookkeeper DATE 4-8-66

APPROVED BY W. A. Gressett TITLE Oil and Gas Inspector DATE APR 11 1966

CONDITIONS OF APPROVAL, IF ANY: