

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 014361-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR J.A. HUBER CORPORATION	8. FARM OR LEASE NAME Standard Federal
3. ADDRESS OF OPERATOR 922 Vaughn Building, Midland, Texas	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 760' PS & 660' FW lines Section 9-20S-24E, Eddy County, New Mexico	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3388.5 GL
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 9-20S-24E
	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

Surface & Intermediate

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 4:00 P.M. 3/29/66. Set 13-3/8" csg. in 17-1/2" hole @ 407' without cement at present time.

Set 8-5/8" csg. in 12-1/4" hole @ 1017' with D.V. Tool at approximately 410'. Cement with 150 sx Class C, 50:50 litepoz + 4% gel + 2% CaCl + 12.5% kolite/sx, followed with 200 sx Class C, 2% CaCl. After cementing will open D.V. Tool and circulate cement above tool cut. Will then close D.V. Tool and drill 7-7/8" hole to T.D.

Upon completion (1) if dry, will recover 8-5/8" csg. above 410' and possibly 13-3/8" csg. and plug well, (2) if productive, will cement between 8-5/8" & 13-3/8" csg. strings with cement thru 1" pipe. Will then cement behind 13-3/8" csg. as necessary.

These plans were approved as per phone conversation with Mr. James Knauf U.S.G.S. Artesia District Engineer.

RECEIVED

APR 25 1966

U. S. G. S.
ARTESIA OFFICERECEIVED
APR 20 1966
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Floyd L. Mendenhall

TITLE

District Prod. Supt.

DATE

4/15/1966

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY.APR 25 1966
Rudolph C. Eater, Jr.
RUDOLPH C. EATER, JR.
ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.