

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
JUL 12 1991  
O. C. D.  
ARTESIA, OFFICE

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other RECOMPLETION

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit A, 330' FNL & 330' FEL, Sec. 8-T19S-R25E

5. Lease Designation and Serial No.  
NM 1372

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Johnston BE #1

9. API Well No.

30-015-20054

10. Field and Pool, or Exploratory Area

North Dagger Draw U/Penn

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☒ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-26-91. RU. Pulled tubing and packer. Laid down excess 2-3/8" tubing. Set CIBP 8950' and cap with 35' cement on top. Ran bond log. Cement top @ 7420'. Perforated Canyon Dolomite with 3-1/8" casing gun, 90 deg phasing, 7853-7899' w/34 - .50" holes as follows: 7853, 57, 60, 62, 71, 72, 73, 81, 82, 83, 87, 89, 91, 93, 95, 97 and 7899' (2 SPF).

6-27-91. Treated perforations 7853-7899' (34 holes) with 10000 gals 20% HCL NEFE acid + 70 ball sealers.

14. I hereby certify that the foregoing is true and correct

Signature *[Signature]*

Title Production Supervisor

Date 7-5-91

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

ACCEPTED FOR RECORD

Date

SJS

JUL 11 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side