

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TWO COPIES
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
069464-A

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME Unit "H"
2. NAME OF OPERATOR E. A. Culberson & Wallace W. Irwin c/o Haynes & V. T. Drilling Co.	8. FARM OR LEASE NAME Federal 18
3. ADDRESS OF OPERATOR 400 First National Bank Bldg., Odessa, Texas	9. WELL NO. 3-0
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Located 2310' from North Line and 330' from East Line of Section 18	10. FIELD AND POOL, OR WILDCAT East Benson Yates
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3426'
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NE 1/4 N.M.P.M. Sec. 18, 19S, 31E
	12. COUNTY OR PARISH Eddy
	13. STATE New Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled plug on 4-1/2" casing set at 2274 - bailed hole dry - cement job okay.

Fractured open hole section 2274-2290 with 10,000 gal. gelled water and 10,000# sand.

Perforated casing with 2 shots per foot 2253-2263. Fractured perforated section with 10,000 gal. gelled water and 7,000# of sand. Shut well in for 12 hours - then released pressure - swabbed fracture fluid and formation oil through casing for 24 hours. Set pump and put to producing September 1, 1968.

RECEIVED

SEP 9 1968

O. C. C.
ARTESIA, OFFICERECEIVED
SEP-5 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AGENT

DATE

Sept. 4, 1968

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
SEP 6 - 1968
R. L. DEEMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.