

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT TO THE DISTRICT ENGINEER
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Gulf Oil Corporation	8. FARM OR LEASE NAME Towers & Federal
3. ADDRESS OF OPERATOR Box 670, Hobbs, New Mexico 88240	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1330' FSL - 1980' FSL, Sec 8, 20-S, 24-E	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
	11. SEC. T. R. S. OR BLK. AND SURVEY OF AREA Sec 8, 20-S, 24-E
	12. COUNTY OR PARISH 13. STATE Eddy New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent to this work.)*

Moran Drilling Company spudded 12-1/4" surface hole at 12:30 AM 2-21-69. Drilled to 900'. Ran 2" joints, 885' of 9-5/8" 32.3# H-40 STC casing set and cemented at 895' with 200 sacks of Class C with 4% gel, 2% Ca Cl₂, 2% tuff plug and 12-1/2# gilsonite per sack and 100 sacks of Class C with 2% Ca Cl₂. Cement did not circulate. TS indicated TOC at 725'. Cemented thru 1" pipe with 50 sacks of Class C with 4% Ca Cl₂ and 50 sacks of Class C with 4% Ca Cl₂ and one sack of cotton seed hulls with each 25 sacks of the second 50 sacks cement and 25 sacks Class C mixed with 10 sacks of Calseal. Cement did not fill to surface. Shovelled 4 yards of 1/2" pea gravel. Gravel bridged near surface. Set 12 sack Class C cement plug to fill 4' below bottom of cellar. Drilled 4 1/2" hole outside 9-5/8" casing to 50' in an attempt to knock out bridge. Unable to drill deeper. Drilled 4 1/2" hole on opposite side of 9-5/8" casing to 65'. Unable to drill deeper. Did not lose circulation. Displaced 4 1/2" holes with 1/2" gravel mixed with 4 sacks of cement. Witnessed by Messrs Charles Saunders and Leon Beekman with U. S. G. S. WOC over 24 hours. Tested casing with 1100', 10 minutes. OK. Drilled cement and shoe. Tested formation and cement job with 500', OK.

Started drilling 8-3/4" hole at 900' at 1:15 AM, February 27, 1969

RECEIVED

MAR 3 1969
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICOO. C. C.
ARTESIA, OFFICE18. I hereby certify that the foregoing is true and correct
ORIGINAL SIGNED BY

SIGNED C. D. BORLAND

TITLE Area Production Manager

DATE February 27, 1969

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED FOR RECORD PURPOSES ONLY

MAR - 3 1969

*See Instructions on Reverse Side

DATE

DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

MAR 8 - 9AM

DATE