

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYForm approved  
Budget Bureau No. 42 R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

1361

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

JUL 9 1976

O. C. C.  
ARTESIA, OFFICE

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> RE-ENTRY	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Yates Petroleum Corporation	8. FARM OR LEASE NAME CC Tank Unit Federal
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM	9. WELL NO. 4
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1830' FSL & 1980' FEL of Sec. 8-20S-24E	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3840 GR
12. COUNTY OR PARISH Eddy	13. STATE NM

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Spud old hole, set Prod Csg. (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in Ard Drilling Company's Rig No. 4. Picked up drill pipe and drilled plugs. Mixed mud and displaced mud, cleaned hole and spudded new hole at 9:30 PM 6-27-76.

TD 9275'; PBTD 9229'. Ran 287 joints of 4½" casing as follows: 22 joints 11.6# N-80 LTC (709'), 69 joints of 11.6# K-55 LTC (2189), 123 joints 10.5# K-55 STC (4027'), 73 joints 11.6# K-55 LTC (2339') (Total 9364') with float shoe at 9261' KB, float collar at 9229' KB, 5 centralizers; cemented w/250 gallons of mud flush, 475 sacks of Halli-Lite .5 of 1% CFR-2, 5# KCL, tailed in w/125 sacks of Class "C" w/3/4% CFR-2 and 5# KCL. Displaced w/20 bbls of 2% KCL and fresh water. PD 9:00 PM 7-1-76. Bumped plug w/1500#. OK. Set slips and cut off landing joint. Released rig.

RECEIVED

JUL - 2 1976

U. S. GEOLOGICAL SURVEY  
ARTESIA, NM

## 18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Geol. Secty

DATE

7-2-76

(This space for Federal or State office use)

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 7 1976

CONDITIONS OF APPROVAL, IF ANY: