

TO : A. J. Deans

DATE: February 9, 1984

RE : Reentry of Hudson Federal #1
Sec. 11, T-18S, R-31E, Eddy County, New Mexico

CASING:

13 3/8" @ 747'
8 5/8" @ 4375'

PLUGS:

1. 10 sx @ surface
2. 100 sx @ shoe of 13 3/8". NOTE: plugging report does not show that this plug was set or any csg POH.
3. 30 sx @ 4320'
4. 50 sx @ 5900'.
5. 30 sx @ 6490'.
6. 50 sx @ 8000'.
7. 60 sx @ 9400'.
8. 100 sx @ 11000'.

REENTRY PROCEDURE:

1. Repair road & location. Dig work over pit.
2. Clean out and install 8' X 8' X 6' cellar.
3. Drill out surface plug with rat hole machine. Set anchors.
4. NU flowline to pit. NU 12 3/4" WO starting head.
5. RU PU & rev unit. MI & RU drilling rig.
6. Drill out to 4300'. Test 8 5/8" to 1500 psi for 30 min. If ok:
7. Drill out to 4600' and condition mud.
8. Rel PU & rev unit. MI & RU drilling rig.
9. GIH w/7 7/8" bit & drilling assembly.
10. Drill out plugs to 8700'. Circulate and condition mud.
11. POH. Run & cmt 5 1/2" csg @ 8700'. Rel Rig.

Peck Hardee
February 9, 1984