

MINERAL COMMISSION  
Drawer DD  
Artesia, NM 88210


Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
2. NAME OF OPERATOR  
Harvey E. Yates Company  
3. ADDRESS OF OPERATOR  
P. O. Box 1933, Roswell, New Mexico 88201  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, SHOW SECTION, TOWNSHIP, RANGE, AND SURVEY OR AREA)  
AT SURFACE: 660' FNL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA



5. LEASE  
LC-062052  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Hudson Federal  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Wildcat - BS  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11 T-18S, R-31E  
12. COUNTY OR PARISH 13. STATE  
Eddy NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3757' GR

- REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐  
SUBSEQUENT REPORT OF:  
☐  
☐  
☐  
☐  
☐  
☐  
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/09/84 Drlg out cmt plug inside surface casing 488' to 748'.  
11/10/84 POH w/12 1/4" Bit. GIH w/11" mill tooth bit. Drill from 748' to 876'.  
11/13/84 Clean out to 1951'. Drill & mill to 2264'. Unable to get inside 8 5/8" casing. Call & get approval to plug from B.L.M. (Bob Pitchski).  
12/14/84 GIH w/71 jts to 2101'. Pump 300 sxs class "C" w/2% CC. POH. SI 4 hrs. GIH & tag @ 1829'. Lay Down 43 jts w/tbg @ 836'. Pump 105 sxs class "C" w/2% CC from 836' to 655'. Dump 50' cmt (35 sxs) @ surface.  
12/15/84 Dry hole marker installed 12/15/84 P & A Completed.

\*NOTE: Int. csg found to be cut off @ 1960'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray L. [Signature] TITLE Reservoir Eng. DATE 12/27/84

Eng. [Signature] (This space for Federal or State office use)

Area Manager

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

10-2484

Post ID- 2  
2-8-85  
PFA