

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructio
verse side)

DATE*

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 092190

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME Dero-Federal (SW-633)	
2. NAME OF OPERATOR Penroc Oil Corporation		8. FARM OR LEASE NAME Dero-Federal	
3. ADDRESS OF OPERATOR P. O. Drawer 831, Midland, Texas 79701		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' EL & 660' SL, Sec. 35, T-19-S, R-28-E		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35-19S-28E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3285"		12. COUNTY OR PARISH Eddy	
		13. STATE N. Mex.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-24-72: Ran 11,319.3' (290 joints) 4½" casing set 2' off bottom
at 11,300' T.D. as follows: 781' 13½", N-80, LT&C
10,107' 11.6", N-80, LT&C
430' 13½", N-80, LT&C

Ran 500 gal. mud flush.

Cemented with 300 sx. 50-50 Pozmix with 8# salt per sack
and .5 of 1% CFR-2, Plug down 1:15 AM, 5-25-72.

Cementer: Halliburton

5-25-72: WOC

5-26-72: Ran temperature survey, top cement 10,060'

RECEIVED

JUN 6 1972

O. C. C.

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Secretary-Treasurer

DATE

5-2-72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUN - 5 1972
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side