					1	
Form 9-331 (May 1963)	N	ITED STATES	5 5	SUBMIT IN	PLICATE.	Form approved. Budget Burcau No. 42-
(1203 100-)	DEPARIME	NT OF THE I	NTERIOR -	verse side)		5. LEASE DESIGNATION AND SERIE
	GEC	LOGICAL SUR	VEY			029388 (d)
CLIN	IDRY NOTICE	S AND DEDC	AND STR	WELLS		6. IF INDIAN, ALLOTTEE OR TRIBE
					oir.	
(	form for proposals Use "APPLICATIO	N FOR PERMIT_"	for such proposals	3.)		
1. OIL GAS						7. UNIT AGREEMENT NAME
WELL WELL	OTHER .	•				
2. NAME OF OPERATOR		i				8. FARM OR LEASE NAME
	chon Oil Comp	any (				Johnson "B" Fed. A/ 9. WELL NO.
3. ADDRESS OF OPERATO		John Norr Mo	wine (	00010		3
	Box 2409, H Report location clear			88240		10. FIELD AND POOL, OR WILDCAT
See also space 17 be At surface	low.)			•••		Snugart lates / Kvr
		тот С 15	TT 100 D	21 5	-	Queen Grayburg 11. sec., t., r., M., OR BLE: AND
660.	FEL & 990' F	SL, Sec. 15,	, 1-105, K-	-DIF		SURVEY OR AREA
					1	Sec. 15, T-18S, R
14. PERMIT NO.	1	5. ELEVATIONS (Show	whether DF, RT, GR,	, etc.)		12. COUNTY OR PARISH 13. STA
Current		GR 3	3695 <b>'</b>			Eddy New M
		D		<		
16.	Check Appro	opriate Box To In	dicate Nature	of Notice, Re	port, or Of	iher Data
	NOTICE OF INTENTION	N TO:	l		SUBSEQUE	ENT REPORT OF:
TEST WATER SHUT-	OFF PULL	OR ALTER CASING		WATER SHUT-OFF		REPAIRING WELL
FRACTURE TREAT		TIPLE COMPLETE		FRACTURE TREATS	dENT .	ALTERING CASING
SHOOT OR ACIDIZE	ABAN	NDON*		SHOOTING OR ACL		ABANDONMENT
REPAIR WELL	СНА	NGE PLANS		(Other)		il string csg.
(Other)		Ĺ		(NOTE: Rep Completion	ort results of or Recomple	of multiple completion on Well tion Report and Log form.)
17. DESCRIBE PROPOSED (	R COMPLETED OPERATI	ions (Clearly state al	ll pertinent detai	ils, and give perti	nent dates, i	including estimated date of start depths for all markers and zone
nent to this work.)		y armea, give subsu	and to the second as	nu menonicu unu		
Drilled to 3505.44', and 1.00' for Bake:	o 3450' TD. set from 10.5 r guide shoe	50' below KDH and insert f	B to 3450'. float. Bo	. Last set ttom two jt	ting de s. Bake	pth includes r locked.
Drilled to 3505.44', and	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600'	B to 3450' float. Bo ing with 30 . Final p	. Last set ttom two jt 00 sacks Tr ump pressur	ting de s. Bake inity L e 1000	4', Overall pth includes r locked. ite Wate psi. Cement
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600'	B to 3450' float. Bo ing with 30 . Final p	. Last set ttom two jt 00 sacks Tr ump pressur	ting de s. Bake inity L e 1000	4', Overall pth includes r locked. ite Wate psi. Cement
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600'	B to 3450' float. Bo ing with 30 . Final p	. Last set ttom two jt 00 sacks Tr ump pressur	ting de s. Bake inity L e 1000	4', Overall pth includes r locked. ite Wate psi. Cement
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 . Final pa ' below su	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	ting de s. Bake inity L ce 1000 D.C. 24	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 . Final p	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	ting de s. Bake inity L ce 1000 D.C. 24	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	ting de s. Bake inity L ce 1000 D.C. 24	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 . Final pa ' below su	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 2.21970
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 2.21970
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. C 200 sacks Cla ate. Top of	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970
Drilled to 3505.44', and 1.00' for Bake: Bottom 400' cer followed with did not circul casing to 1500	o 3450' TD. set from 10.5 r guide shoe ntralized. (2 200 sacks Cla ate. Top of psi, held 0.	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970
Drilled to 3505.44', and 1.00' for Bake Bottom 400' cer followed with did not circul	o 3450' TD. set from 10.5 r guide shoe ntralized. (2 200 sacks Cla ate. Top of psi, held 0.	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pu below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 2.2 1970
Drilled to 3505.44', and 1.00' for Bake: Bottom 400' cer followed with did not circul casing to 1500	o 3450' TD. set from 10.5 r guide shoe ntralized. (2 200 sacks Cla ate. Top of psi, held 0.	below KDF and insert f Cemented casi ass C cement. cement 1600 K. ARTESI ue and correct	B to 3450' float. Bo ing with 30 Final pa below su below su 3 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970
Drilled to 3505.44', and s 1.00' for Bake: Bottom 400' cer followed with s did not circul casing to 1500	o 3450' TD. set from 10.5 r guide shoe ntralized. (2 200 sacks Cla ate. Top of psi, held 0.	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K.	B to 3450' float. Bo ing with 30 Final pr below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 2.2 1970
Drilled to 3505.44', and a 1.00' for Bake: Bottom 400' cer followed with a did not circula casing to 1500 18. I hereby certify tha SIGNED	t the foregoing is tr	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K. ARTESL ue and correct Tr ise)	B to 3450' float. Bo ing with 30 Final pa below su below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970 221970 DATE July 17,
Drilled to 3505.44', and a 1.00' for Bake: Bottom 400' cer followed with a did not circula casing to 1500 18. I hereby certify tha SIGNED	t the foregoing is tr	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K. ARTESL ue and correct 	B to 3450' float. Bo ing with 30 Final pr below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 2.2 1970
Drilled to 3505.44', and 1.00' for Bake: Bottom 400' cer followed with 3 did not circul casing to 1500 18. I hereby certify tha SIGNED	t the foregoing is tri deral or State office v	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K. ARTESL ue and correct 	B to 3450' float. Bo ing with 30 Final pa below su below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970 221970 DATE July 17,
Drilled to 3505.44', and 1.00' for Bake: Bottom 400' cer followed with 3 did not circul casing to 1500 18. I hereby certify tha SIGNED	t the foregoing is tri deral or State office v	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K. ARTESL ue and correct 	B to 3450' float. Bo ing with 30 Final pa below su below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.C	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970 221970 DATE July 17,
Drilled to 3505.44', and 1.00' for Bake: Bottom 400' cer followed with 3 did not circul casing to 1500 18. I hereby certify tha SIGNED	t the foregoing is tri deral or State office v	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K. ARTESI ue and correct Tr ise) TT	B to 3450' float. Bo ing with 30 Final pa below su below su 5 1970	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.O	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970 221970 DATE July 17,
Drilled to 3505.44', and a 1.00' for Bake: Bottom 400' cer followed with a did not circula casing to 1500 18. I hereby certify that SIGNED	t the foregoing is tri deral or State office v	50' below KDF and insert f Cemented casi ass C cement. cement 1600' .K. ARTESI ue and correct Tr ise) TT	B to 3450' float. Bo ing with 30 Final pr below su below su 5 1970 A, L	. Last set ttom two jt 00 sacks Tr ump pressur rface. W.O	REC	4', Overall pth includes r locked. ite Wate psi. Cement hrs. Tested 221970 221970 DATE July 17,