

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
N. M. O. C. C. COPY
SUBMIT IN THE STATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

0352858-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil Fed. CI

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Penasco Draw SA geo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 6-19S-25E

Unit J NMMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface 1980' FSL & 1980' FEL of Sec. 6-19S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3617' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETES ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud & set 7" casing ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-6-72 - Spudded 9 7/8" hole at 5:00 PM 3-6-72.

3-7-72 - Ran 950' of 7" 24# J-55 w/shorty shoe(casing) set at 950' w/575 sacks as follows: Centralizers at 553 & 490', baskets at 522 & 460'. Cemented casing with 200 sx Incor mix 2% CaCl followed by 100 sx Incor Neat 2% CaCl. PD 6:15 PM 3-7-72. Cement did not circulate. WOC 8 hrs, ran Temperature Survey, top of cmt at 605'. Ran 1" tubing to 500'. Spotted 75 sx Incor Neat 4% CaCl. PD 4 AM 3-8-72. WOC 4 1/2 hrs, tagged firm cmt at 490'. Spotted 75 sx Incor Neat 4% CaCl. PD 9 AM 3-8-72. WOC 2 1/2 hrs, tagged firm cmt at 478'. Spotted 75 sx Incor Neat 4% CaCl. PD 11:15 AM 3-8-72. WOC 3 1/2 hrs., tagged cement at 440'. Layed down 1" and bradenheaded 50 sx Incor Mix 4% CaCl and filled hole with 9 1/2 yards of Ready-Mix. WOC 24 hours, nipples up and pressure tested casing to 500#. Tested OK. Drilled shoe and pressured to 500#, tested OK. Reduced hole to 6 1/2" and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

3-14-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
MAR 14 1972
R. L. BECKMAN
ACTING DISTRICT ENGINEERRECEIVED
MAR 14 1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

*See Instructions on Reverse Side