

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Copy 7-5-73

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0473362

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DWU-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Winchester-Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 34, T-19-S, R-28-E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Dorchester Exploration, Inc.

JUN 23 1973

3. ADDRESS OF OPERATOR

1204 Vaughn Building, Midland, Texas 79701 D. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)At surface 1980' from South line & 1980' from East line of
Section 34, T-19-S, R-28-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3307 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Dec. 20, 1972 Spudded well at 2:00 p.m.

Dec. 21, 1972 Ran 317' 13-3/8" 52.5# Csg. Set at 301'. Cemented with 300 sx Class C 2% CaCl. Circulated to surface. WOC 18 hrs. Tested Csg. to 1000 psi with rig pump and held 30 min. No leak.

Dec. 29, 1972 TD 3030'. Ran 76 jts. of 8-5/8" 24# and 32# Csg. Length of string 3043'. Set at 3030'. Cemented with 775 sax light weight cement plus 200 sax Class C neat cement. After 10 hrs. ran temp. survey and found top of cement at 675'.

Dec. 30, 1972 W.O.C. 18 hrs. Tested csg. to 1500 psi with rig pump and held 30 min. No leak.

Change operator from Robert R. Hillier

RECEIVED

JUN 27 1973

B. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE June 25, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 27 1973

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.