

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp.</u>		Lease <u>State C.O.</u>		Well # <u>1</u>	
Location of Well	Unit <u>1980S+U</u>	Section <u>36</u>	Township <u>19</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor <u>Cactus Corp.</u>	Type of Equipment <u>Rotary to start approx. 6-22-73</u>				
APPROVED CASING PROGRAM 6-18-73					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48</u>		<u>215</u>	<u>150 cin.</u>
<u>12 1/4"</u>	<u>9 5/8"</u>	<u>32.30</u>		<u>975</u>	<u>500 cin.</u>
<u>8 3/4"</u>	<u>7"</u>	<u>23+26"</u>		<u>6500</u>	<u>200</u>
Casing Data:					
Surface <u>32</u> joints of <u>9 5/8"</u> inch <u>32.30</u> # Grade <u>API New</u>					
(Approved) (Rejected)					
Inspected by <u>L. A. Gilemis</u> date <u>6-29-73</u>					
Cementing Program					
Size of hole <u>12 1/4"</u> Size of Casing <u>9 5/8"</u> Sacks cement required <u>400</u>					
Type of Shoe used <u>Texaco</u> float collar used <u>None</u> Btm 3 jts welded <u>Threadlock</u>					
TD of hole <u>992 KB</u> Set <u>979</u> feet of <u>9 5/8"</u> inch <u>32</u> # Grade <u>API New</u>					
New-used csg. @ <u>979</u> with <u>150</u> sacks neat cement around shoe Class C 2% CC 15.0					
+ <u>250</u> sax <u>3% Celofane</u> additives <u>6% Silsonite</u> 2% CC 14.0					
Plug down @ <u>6:00</u> (AM) (PM) Date <u>7-1-73</u>					
Cement circulated <u>No</u> No. of Sacks <u>None</u>					
Cemented by <u>Denton</u> Witnessed by <u>L. A. Gilemis</u>					
Temp. Survey ran @ <u>1:45</u> (PM) (PM) Date <u>7-1-73</u> top cement @ <u>450</u>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Surface TD 225 KB 17 1/2' hole 13 3/8" New API 48" csg. Set</u>					
<u>215' GL 150/sx Neat 4% CC Incor. 14.0" Did Not Circ Filled hole to</u>					
<u>surface with ready mix. 500' 491'</u>					
<u>One inch info on slotted mix. 200/sx Class C 2% CC top. 63'</u>					
<u>filled hole to surface with ready mix.</u>					
<u>Conty. 900', 500', 400' each. 491', 411'</u>					
<u>Plugged 8-20-73 35/sx 9075-9175, 8500-8900, 40/sx 7800-7900</u>					
<u>75/sx 6100-6300, 40/sx 3900-4000, 2000-2100, 950-1050,</u>					
<u>101/sx surface.</u>					