

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instruction on re-
verse side)

Form approved 70 51
Budget Bureau No. 42-R1424

NMOCC COPY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR MONSANTO COMPANY ✓		8. FARM OR LEASE NAME DAGGER DRAW	
3. ADDRESS OF OPERATOR 1330 Midland NBT, Midland, Texas 79701		9. WELL NO. 2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FWL & 1980' FSL Section 8		10. FIELD AND POOL, OR WILDCAT Cemetery - Morrow Gas	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3513 Gr.	
		12. COUNTY OR PARISH Eddy	
		13. STATE N.M.	

RECEIVED

JAN 5 1978

O.C.C.
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Attempt to salvage 5 1/2" casing where indicated free.

Cement plugs as follows:

Set CIBP w/ 20' cmt on top @ 6270'
100' Cmt plug 50' below 5 1/2" Casing cut
100' Cmt Plug 50' above 5 1/2" casing cut
100' Cmt Plug across shoe of intermediate casing
20' Cmt plug at surface

Hole between plugs will be filled with better than 25% Gel per Bbl Water;
4" pipe marker with location thereon will be set at surface.

RECEIVED
DEC 21 1977
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Regional Prod. Mgr.

DATE 12/20/77

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE JAN 4 - 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side