

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SEP 17 1974

O. C. C.

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator SAMEDAN OIL CORPORATION	5. State Oil & Gas Lease No.
3. Address of Operator 2207 Wilco Bldg., Midland, Texas 79701	7. Unit Agreement Name
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 2310 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 19-S RANGE 26-E NMPM.	8. Farm or Lease Name Nix
15. Elevation (Show whether DF, RT, GR, etc.) 3340' G. L.	9. Well No. 1
	10. Field and Pool, or Wildcat Undesignated Morrow
	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Hondo Drilling Co. rigged up and spudded 12 $\frac{1}{4}$ " hole at 9:00 P.M. September 6, 1974. Drilled to 1165' and set 8 5/8", 24#, K55, ST & C casing at 1153' and cemented with 100 sacks 50-50 POZ - mix with 12% gel and 375 sacks lite weight with ~~5#~~ 5# Gilsonite per sack, and 1/4 Floseal per sack with 2% calcium chloride and 200 sacks Class "C" with 2% calcium chloride. Cement did not circulate. W. O. C. 6 hours, ran temp. survey found cement top at 475'. Ran 1" to 460' and pumped 350 sacks Class "C" with 4% calcium chloride had full returns, cement did not circulate, waited 2 hours and tagged cement at 45'. Pumped 150 sacks Class "C" with 4% calcium chloride, cement circulated. W. O. C. 24 hours tested casing to 1,000 psi, no pressure loss. Drilling ahead.

This copy has been corrected in red. The 50-50 Poz-mix had 12% gel. Lite weight Cnt does not have gel.

*Re-file form C-103 with these corrections. Thank You
Lelan Mermis*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed *William S. McCuen*

TITLE Production Superintendent

DATE 9-16-74

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: