

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLA E*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029392 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 26

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Shugart

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 26-18S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Honeysuckle Exploration Corp.

3. ADDRESS OF OPERATOR
450 Petroleum Club Building, Denver, CO 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1880' FSL, 1880' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3660 Gr

O. C. C.
ARTESIA, OFFICE

RECEIVED
AUG 12 1976

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	ABANDON*	<input type="checkbox"/>
REPAIR WELL	CHANGE PLANS	<input type="checkbox"/>
(Other)		<input type="checkbox"/>

WATER SHUT-OFF	<input checked="" type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
(Other)			<input type="checkbox"/>

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well 12 1/4" hole on 7-27-76, drilled to 1144'. Ran and set 8 5/8" casing to 897. Cemented with 575 sx Class C cement - circulated 36 bbl excess to surface. Waited 18 hours, tested to 800 PSI - OK. Drilled ahead below 8 5/8" casing

RECEIVED

AUG 11 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

John C. Seely

TITLE

President

DATE

8-3-76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
103
D. L. BEEKIN
D. L. BEEKIN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side