

MOCC COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well or to enlarge an existing well or to enlarge an existing reservoir. Use Form 9-331-C for such proposals.)

MAR 28 1979

1. oil ☐ gas ☒ other

O. C. C.

ARTESIA, OFFICE

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P.O. Drawer "A", Levelland, TX 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650' FNL & 1980' FWL, Sec 35
AT TOP PROD. INTERVAL: (Unit F, SE/4 NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

MAR 28 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to TD of 4600' (3/7/79) and set 9 5/8" 36# K-55 (3220') & S-80 (1380') ST & C casing at 4600'. Cemented with 1550 sx BJ Lite and 200 sx Class C cement with 2% CACL. Circulated 75 sx. Plugged down 2:30 a.m. 3/8/79. WOC 18 hrs. Tested casing with 1000# for 30 minutes. Tested O.K. Reduced hole to 8 3/4" and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Cox TITLE Admin. Supervisor DATE March 20, 1979

(This space for Federal or State office use)

APPROVED BY Lee A. Lara
CONDITIONS OF APPROVAL, IF ANY:

ACTING DISTRICT ENGINEER

MAR 23 1979

0+4-USGS, A
1-Hou
1-RWA
1-Susp

*See Instructions on Reverse Side