

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	H
U.S.G.S.	
LAND OFFICE	
OPERATOR	✓

**RECEIVED.**  
 NEW MEXICO OIL CONSERVATION COMMISSION  
**MAY 28 1979**  
 CORRECTED COPY  
**O. C. C.**  
**ARTESIA, OFFICE**

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease  
 State  Fee   
 5. State Oil & Gas Lease No.  
**E-2943**

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO OIL OR GAS RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator <b>Southland Royalty Company ✓</b> 3. Address of Operator <b>1100 Wall Towers West, Midland, Texas 79701</b> 4. Location of Well UNIT LETTER <b>O</b> <b>990</b> FEET FROM THE <b>south</b> LINE AND <b>1980</b> FEET FROM THE <b>east</b> LINE. SECTION <b>16</b> TOWNSHIP <b>19S</b> RANGE <b>29E</b> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) <b>3339.1' GR</b>	7. Unit Agreement Name 8. Farm or Lease Name <b>State "16A" Com.</b> 9. Well No. <b>1</b> 10. Field and Pool, or Wildcat <b>Turkey Track (Morrow)</b> 12. County <b>Eddy</b>
--	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER _____ <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER _____ <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>
--	---

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud at 11:30 A.M. 5-22-79 by Hondo Drlg. Co. Rig #5. Drill 15" hole to 280'. Ran 11 3/4" 43# H-40 ST&C csg. set @ 280'.  
 Cement w/300 sx Class "C" cement w/2% c.c. Plug down @ 7:15 A.M. 5-23-79. Cement did not circ. Fill back side w/8 cu. yds cmt. to circ. Install 10" Ser 900 BOP. Test 11 3/4" csg. and BOP to 1000 psi for 30 min; hold o.k. Drill ahead 11" hole.

CORRECTED REPORT

NOTE: WOC 18 hours prior to testing casing and BOP.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Harvey Carr TITLE District Engineer DATE 5-24-79  
 APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 15 1979  
 CONDITIONS OF APPROVAL, IF ANY: